

COSMOTHENE® G810-S

Low Density Polyethylene

TPC, The Polyolefin Company (Singapore) Pte Ltd

Message:

COSMOTHENE® G810-S is a Low Density Polyethylene product. It can be processed by injection molding and is available in Asia Pacific.

Characteristics include:

Good Flexibility

Good Processability

High ESCR (Stress Crack Resistant)

General Information			
Features	Good Flexibility		
	Good Moldability		
	High ESCR (Stress Crack Resist.)		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.918	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	35	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	9.81	MPa	ASTM D638
Tensile Elongation (Break)	600	%	ASTM D638
Apparent Bending Modulus	157	MPa	ASTM D747
Thermal	Nominal Value	Unit	
Melting Temperature	105	°C	
Injection	Nominal Value	Unit	
Processing (Melt) Temp	170 to 200	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT