

PSM® HL-100B2F

Thermoplastic

Wuhan Huali Environmental Technology Co., Ltd.

Message:

PSM®HL-100B2F is a thermoplastic material. This product is available in the Asia-Pacific region. PSM®The main characteristics of the HL-100B2F are: environmental protection/green.

| General Information | | | |
|-----------------------------|---------------------|-------------------|--------------|
| Features | Updatable resources | | |
| Physical | Nominal Value | Unit | Test Method |
| Density | 1.10 - 1.30 | g/cm ³ | ISO 1183 |
| Melt Mass-Flow Rate (MFR) | 1.0 - 2.5 | g/10 min | ISO 1133 |
| Biobased Content | 52 | % | ASTM D3856 |
| Moisture | | % | |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Stress | 8.00 - 14.0 | MPa | ISO 527-2 |
| Thermal | Nominal Value | Unit | Test Method |
| Vicat Softening Temperature | 135 - 140 | °C | ISO 306/B120 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

