

# Jam HDPE HM9455F1

High Density Polyethylene

Jam Petrochemical Company

## Message:

Jam HDPE HM9455F1 is a High Density Polyethylene product. It is available in Africa & Middle East. Typical application: Film.

General Information			
Physical	Nominal Value	Unit	Test Method
Uses	Film		
Density	0.957 to 0.961	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	5.5 to 9.5	g/10 min	ISO 1133
Flow Rate Ratio <sup>1</sup>	30.0 to 38.0		
Fish Eye	< 3.00		Internal Method
NOTE			

1.

5/2.16, FRR values are statistical and calculated by dividing MFR values.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

