Indothene LL 20FS020

Linear Low Density Polyethylene Reliance Industries Limited

Message:

Indothene LL 20FS020 is a Linear Low Density Polyethylene product. It is available in Africa & Middle East or Asia Pacific. Typical application: Film.

General Information			
Uses	Film		
Forms	Granules		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/	72.16		
kg)	2.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Coefficient of Friction	0.15		ASTM D1894
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD : Break	29.4	MPa	
TD : Break	24.5	MPa	
Tensile Elongation			ASTM D882
MD : Break	800	%	
TD : Break	950	%	
Dart Drop Impact	90	g	ASTM D1709
Elmendorf Tear Strength			ASTM D1922
MD	200	g	
TD	400	g	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

