THERMOLAST® K TC6UVZ (Series: UV/AP)

Thermoplastic Elastomer

KRAIBURG TPE

Message:

The UV/AP Series is your material solution for applications requiring high UV resistance. It is particularly suited for automotive exterior components. The compounds comply with GM standard GMW 16233.

Typical applications

Roof rims

Water deflectors

Window encapsulations

Material advantages

Adhesion to PP

Easy flowing

Excellent mechanical properties

Excellent UV- and weather resistance

General Information				
Features	Good Adhesion Good Flow			
	Good UV Resistance			
	Good Weather Resistance			
Uses	Automotive Exterior Parts			
Appearance	Black			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Density	1.19	g/cm³	ISO 1183	
Hardness	Nominal Value	Unit	Test Method	
Shore Hardness (Shore A)	60		ISO 868	
Elastomers	Nominal Value	Unit	Test Method	
Tensile Stress ¹ (Yield)	5.20	MPa	ISO 37	
Tensile Elongation ² (Break)	600	%	ISO 37	
Tear Strength ³	20	kN/m	ISO 34-1	
Compression Set ⁴			ISO 815	
23°C, 72 hr	21	%		
70°C, 24 hr	52	%		
100°C, 24 hr	72	%		
Injection	Nominal Value	Unit		
Drying Temperature	60.0 to 80.0	°C		
Drying Time	2.0 to 4.0	hr		
Rear Temperature	180	°C		
Middle Temperature	200	°C		
Front Temperature	220	°C		

Mold Temperature	25.0 to 40.0	°C	
Injection Pressure	20.0 to 100	MPa	
Back Pressure	2.00 to 10.0	MPa	
NOTE			
1.	Type S2, 200 mm/min		
2.	Type S2, 200 mm/min		
3.	Method Bb, Angle (Nicked)		
4.	Method A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

