

Supol HP1700E

Polypropylene Copolymer

LyondellBasell Industries

Message:

SUPOL HP1700E is an unfilled UV resistant polypropylene copolymer compound for injection moulding. Designed for automotive applications it is available in custom colours.

General Information			
Additive	UV Stabilizer		
Features	Copolymer		
	High Flow		
	Low Density		
	Medium Rigidity		
Uses	Automotive Interior Parts		
Appearance	Colors Available		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	40	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	1400	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	5.0	kJ/m ²	ISO 180/1A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT