

Epoxies, Ect. 60-7105

Polyurethane
Epoxies, Etc.

Message:

UV Cure 60-7105 is a low viscosity urethane adhesive, coating and potting compound. This UV curable resin exhibits outstanding adhesion, toughness, and exterior durability. UV Cure 60-7105 does not contain any solvents and is therefore a 100% solids system. This material is a good choice for deep section curing.

Features:

- Low viscosity
- Exterior durability
- Good toughness
- Excellent adhesion to difficult substrates

General Information		
Features	Durable	
	Good Adhesion	
	Good Toughness	
	Low Viscosity	
Uses	Adhesives	
	Coating Applications	
Appearance	Clear/Transparent	
Processing Method	Potting	
Additional Information	Nominal Value	Unit
Operating Temperature	-55.0 to 155	°C
Uncured Properties	Nominal Value	Unit
Color	Clear/Transparent	
Viscosity (25°C)	3.0	Pa·s
Shelf Life (30°C)	1	month
Cured Properties	Nominal Value	Unit
Shore Hardness (Shore D)	78	
Tensile Strength	34.5	MPa
Tensile Elongation at Break	20	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

