

Trovidur® W 2000

Flexible Polyvinyl Chloride

Röchling Engineering Plastics SE & Co. KG

Message:

- Product characteristics
- Raised chemical resistance
- Tough and abrasion-resistant
- Excellent adherability
- Typical field of application
- Chemical engineering and tank building
- Environment and disposal technology

General Information			
Features	Bondability		
	Good Abrasion Resistance		
	Good Adhesion		
	Good Toughness		
Uses	Engineered Applications		
	Tanks		
Physical	Nominal Value	Unit	Test Method
Density	1.31	g/cm³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	85		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Strain (Break)	250	%	ISO 527-2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT