

# Sinpolene MBB2401

Linear Low Density Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

## Message:

SINPOLENE MBB2401 is a modified copolymer based black masterbatch designed specifically for use in injection moulding, tubular film blowing, blow moulding and extrusion of polyolefins. SINPOLENE MBB2401 has high pigment loading and thus offers high coloring value with superior quality and performance.

SINPOLENE MBB2401 is delivered as free flowing pellets for processing convenience.

### CHARACTERISTICS

- \* Easy processing
- \* Good dispersion
- \* High jetness
- \* Minimal wear effect on processing equipment

General Information	
Features	General
Uses	Films
	Sheet
RoHS Compliance	RoHS compliance
Forms	Particle
Processing Method	Blow film
	Sheet extrusion molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.16	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/10.0 kg)	< 30	g/10 min	ASTM D1238
Moisture Content		%	ASTM D3030
Carbon Black Content	40	%	ASTM D1603

Additional Information
Recommended dosage: 2 - 5%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT