Jackdaw PP EV13BN6469

Polypropylene

Jackdaw Polymers

Message:

Jackdaw PP EV13BN6469 is a Polypropylene product. It is available in Europe. Primary characteristic: flame rated.

General Information			
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.970	g/cm³	ASTM D792, ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	35.0	MPa	ASTM D638, ISO 527-2
Tensile Elongation (Break)	6.0	%	ASTM D638, ISO 527-2
Flexural Modulus	1900	MPa	ASTM D790, ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	17	kJ/m²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	180	°C	ASTM D2117, ISO 1218
Flammability	Nominal Value		Test Method
Flame Rating	НВ		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

