

ExxonMobil™ PP3155E3

Polypropylene Homopolymer

ExxonMobil Chemical

Message:

A homopolymer resin designed for spunbond technology. The resin has excellent performance, is suitable for uniform and continuous spinning, and can spin high-quality fabrics at high speed. Contains stabilizer packages specially formulated to resist gas fading and suitable for non-woven fabrics and filament products.

General Information	
Features	Resistance to gas fading Workability, good
Uses	Spunbond nonwoven fabric Personal care Industrial application Fiber Medical/nursing supplies
Appearance	Natural color
Forms	Particle
Processing Method	Spunbond Nonwovens Filament extrusion

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	36	g/10 min	ASTM D1238

Legal statement
有关潜在食品接触应用合规信息(例如:FDA,EU,HPFB),请与埃克森美孚化工客户服务代表联系.未经埃克森美孚化工书面允许,这种产品包括其产品名称,不得在任何医疗应用领域予以使用或

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT