

Fixmaster NC Super Metal

Epoxy; Epoxide

Loctite®

Message:

Fixmaster NC Super Metal is an Epoxy; Epoxide (Epoxy) product. It is available in North America. Applications of Fixmaster NC Super Metal include coating applications, industrial applications and repairing material.

Characteristics include:

Chemical Resistant

Corrosion Resistant

Lubricated

Wear Resistant

General Information			
Additive	Silicone Lubricant		
Features	Good Abrasion Resistance		
	Good Chemical Resistance		
	Good Corrosion Resistance		
	Lubricated		
Uses	Industrial Applications		
	Metal Repairing Material		
	Protective Coatings		
Appearance	Grey		
Forms	Pellets		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore D)	95		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	48.3	MPa	ASTM D638
Compressive Strength	124	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	121	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Volume: 1.0		
Resin	Mix Ratio by Volume: 5.0		
Pot Life (25°C)	20 to 30	min	
Demold Time (25°C)	180 to 240	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

