

WPP PP WPP331H

Polypropylene Copolymer
Washington Penn Plastic Co. Inc.

Message:

WPP PP WPP331H is a polypropylene copolymer (PP Copoly) product. It is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Typical application areas are: automotive industry.
Features include:
High stiffness
Copolymer
Good toughness
Impact resistance
Wear-resistant

General Information			
Features	Rigidity, high		
	Copolymer		
	Impact resistance, high		
	Durability		
	Good toughness		
Uses	Application in Automobile Field		
	Car interior equipment		
	Automotive exterior parts		
Appearance	Available colors		
Physical	Nominal Value	Unit	Test Method
Density	0.890	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	11	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			ISO 527-2/50
Yield	20.0	MPa	ISO 527-2/50
Fracture	20.0	MPa	ISO 527-2/50
Flexural Modulus ¹	960	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	39	kJ/m ²	ISO 180
Additional Information			
Tested at 23 ± 2°C (73.4 ± 3.6°F) and 50 ± 5% relative humidity unless otherwise noted.			
NOTE			
1.	2.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT