

Aropol™ 7320-1

Thermoset Polyester

Ashland Performance Materials

Message:

Ashland resins for the electrical market
Chemistry
Iso Polyester
Performance Attributes
Medium viscosity. Resilient. High Impact Strength. Toughness. Chemically thickenable
Comments
General Purpose. Can be used in SMC, BMC, and wet mat molding. All ingredients are FDA approved

General Information		
Features	General Purpose	
	Good Toughness	
	High Impact Resistance	
	Medium Viscosity	
	Resilient	
Uses	Electrical/Electronic Applications	
	General Purpose	
Agency Ratings	FDA Unspecified Rating	
Physical	Nominal Value	Unit
Solution Viscosity	2900	mPa · s
Gardner Color	< 2.00	
Uncured Properties	Nominal Value	Unit
Gel Time	5.0	min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT