Propafilm™ RGR02/120

Polypropylene Alloy

Innovia Films Ltd.

General Information

Message:

One Side Treated Release Film

Biaxially oriented polypropylene (BOPP) film co-extruded on both sides with surface polymers.

RGR02/60 &120 are particularly suited for tape and release applications, in which RGR02 could be reverse printed and laminated to another web.

ROR02/60 is suited for the outer web of foil laminations used in condiment sachet applications.

Features	Excellent Printability		
	Food Contact Acceptable		
	Good Impact Resistance		
	Low Temperature Impact Resistan	ce	
	Puncture Resistant		
Uses	Bi-axially Oriented Film		
	Food Service Applications		
	Laminates		
	Packaging		
Forms	Film		
Processing Method	Blown Film		
	Coextrusion		
Physical	Nominal Value	Unit	Test Method
Molding Shrinkage - Flow (129°C, 1 min)	6.0	%	Internal Method
Mechanical	Nominal Value	Unit	Test Method
Coefficient of Friction			ASTM D1894
vs. Itself - Dynamic, Outside/Outside	0.30		
vs. Itself - Static, Outside/Outside	0.30		
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	3000	μm	
Secant Modulus ¹			ASTM D882
1% Secant, MD	2490	MPa	
1% Secant, TD	2090	MPa	
Tensile Strength ²			ASTM D882
MD : Yield	230	MPa	
TD : Yield	190	MPa	
Tensile Elongation ³			ASTM D882
3			

TD : Break	130	%		
Oxygen Permeability (23°C, 0% RH)	41	cm³·mm/m²/atm/24 hr	ASTM F1927	
Water Vapor Transmission Rate (38°C, 90%				
RH)	5.0	g/m²/24 hr	ASTM F1770	
Corona Treatment	38	dyne/cm	Internal Method	
Yield	36.7	m²/kg	Internal Method	
NOTE				
1.	10%/min			
2.	50%/min			
3.	50%/min			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

