

Geon™ Vinyl Flexible R2495A

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™ Vinyl Flexible R2495A is a Flexible Polyvinyl Chloride product. It can be processed by extrusion or profile extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Geon™ Vinyl Flexible R2495A include hose/tubing and automotive. Characteristics include:

Low Gloss

UV Stabilized

General Information	
Additive	UV Stabilizer
Features	Low Gloss
	UV Absorbing
Uses	Automotive Bumper
	Hose
	Profiles
	Tubing
Forms	Pellets
Processing Method	Extrusion
	Profile Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.45	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	82		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Break)	1.38	MPa	ASTM D638
Tensile Elongation ² (Break)	280	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-20.0	°C	ASTM D746
Extrusion	Nominal Value	Unit	
Melt Temperature	179 to 185	°C	
NOTE			
1.	Type IV, 510 mm/min		
2.	Type IV, 510 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT