

Pujie CM35L

Chlorinated Polyethylene

Zhanhua Pujie Chemical Technology Co.,Ltd

Message:

CM35L, Medium to low molecular weight, Mooney viscosity between 50 and 65, superior mechanical performances, applied in many fields and with good processibility

General Information		
Features	Workability, good	
	Medium molecular weight	
Uses	Cable sheath	
	Pipe	
Physical	Nominal Value	Unit
Apparent Density	> 0.50	g/cm ³
Mooney Viscosity (ML 1+4, 125°C)	50 - 65	MU
Chlorine Content	34.0 - 36.0	wt%
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	< 57	
Mechanical	Nominal Value	Unit
Tensile Strength	> 8.00	MPa
Tensile Elongation (Break)	> 700	%
Thermal	Nominal Value	Unit
Heat of Fusion		J/g
Impurities		pcs/50 g
Volatiles		%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

