

Petrothene® PM92973

Linear Low Density Polyethylene

LyondellBasell Industries

Message:

PETROTHENE PM92973 is a black concentrate formulated to be used with PETROTHENE GA808091, a natural LLDPE let-down resin, for use in the extrusion of communications and power cable jacketing. Antioxidant, to ensure long- term stability, and a processing aid have been added. This resin can be successfully used with LDPE, LLDPE, MDPE, HDPE and PP resins.

General Information			
Additive	Carbon Black (40%)		
Uses	Blending		
	Cable Jacketing		
	Power Cable Jacketing		
	Telecommunications		
	Wire & Cable Applications		
Appearance	Black		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.14	g/cm ³	ASTM D1505
Carbon Black Content	40	%	ASTM D1603

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

