

Pro-fax PH835

Polypropylene Homopolymer

LyondellBasell Industries

Message:

Pro-fax PH835 polypropylene homopolymer is available in pellet form. This resin is typically used in spunbond and continuous filament applications that require superior spinnability and finer fibers.
For regulatory compliance information see Pro-fax PH835 Product Stewardship Bulletin (PSB).

General Information	
Features	Gas-fading Resistant
	Good Processing Stability
	Homopolymer
Uses	Fibers
	Filaments
	Film
	Food Packaging
	Media Packaging
	Nonwovens
	Spun Bonding
	Staple Fibers
Forms	Pellets
Processing Method	Extrusion Coating
	Fiber (Spinning) Extrusion
	Filament Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.898	g/cm ³	ASTM D792B
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	34	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT