

# Ad-Tech Epoxy EL-325-1-HTTC

Epoxy; Epoxide

Ad-Tech Plastic Systems Corp.

## Message:

Ad-Tech Epoxy EL-325-1-HTTC is an Epoxy; Epoxide (Epoxy) product. It can be processed by laminating and is available in North America. Applications of Ad-Tech Epoxy EL-325-1-HTTC include coating applications, prototyping applications and tools. Primary characteristic: good dimensional stability.

General Information		
Features	Good Dimensional Stability	
	Non-MDA Cured	
Uses	Laminates	
	Modeling Material	
	Tooling	
Appearance	Grey	
Forms	Pellets	
Processing Method	Laminating	
Thermoset	Nominal Value	Unit
Thermoset Components		
	Mix Ratio by Volume: 1.0	
Hardener	Mix Ratio by Weight: 29	
	Mix Ratio by Weight: 100	
Resin	Mix Ratio by Volume: 3.8	
Pot Life (25°C)	180	min
Demold Time		
25°C	2900	min
66°C	180	min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

