

# ICORENE® 9105 V0 Grey 7004

Linear Low Density Polyethylene

ICO Polymers EMEA, A Division of A. Schulman

## Message:

ICORENE® 9105 V0 Grey 7004 is a linear low density polyethylene containing a flame retardant additive package for use in rotational moulding applications.

This grade comply with the requirements to meet UL94 V0 at 5mm thickness.

ICORENE® 9105 V0 Grey 7004 is recommended for indoor applications.

General Information			
Additive	Flame Retardant 1		
Features	Good UV Resistance		
Uses	General Purpose		
Appearance	Light Grey		
Forms	Powder		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density	> 1.00	g/cm <sup>3</sup>	ASTM D1505
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	17.0	MPa	
Break	7.00	MPa	
Tensile Elongation			ASTM D638
Yield	19	%	
Break	50	%	
Flexural Modulus	750	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	7.0	kJ/m <sup>2</sup>	ISO 179
Flammability	Nominal Value		Test Method
Flame Rating (5.00 mm)	V-0		IEC 60695-11-10

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT