

Baynat® 755 Isocyanate

Polyurethane

Covestro - PUR

Message:

Baynat 755 polyurethane foam system is used in automotive headliner applications. This system allows low weight, good thermal dimensional stability, and high definition of surface structure. As with any product, use of Baynat 755 system in a given application must be tested (including but not limited to field testing) in advance by the user to determine suitability.

The Baynat 755 system is supplied as two reactive liquid components. Component A is a polyisocyanate. Component B is a polyether polyol mixture.

General Information		
Forms	Liquid	
Physical	Nominal Value	Unit
Specific Gravity		
-- ¹	1.02	g/cm ³
-- ²	1.24	g/cm ³
Apparent Density		
-- ³	1.02	g/cm ³
-- ⁴	1.23	g/cm ³
Flammability	Nominal Value	Unit
Flash Point - PMCC		
-- ⁵	122	°C
-- ⁶	199	°C
Additional Information		
Appearance, Part A: Dark brown to black liquidAppearance, Part B: Colorless liquid		
NOTE		
1.	Part B	
2.	Part A	
3.	Part B	
4.	Part A	
5.	Part B	
6.	Part A	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT