

# DIAREX® H350

High Impact Polystyrene

PTT Global Chemical Public Company Limited

## Message:

DIAREX® H350 is a High Impact Polystyrene material. It is available in Asia Pacific.

Important attributes of DIAREX® H350 are:

Flame Rated

Impact Resistant

General Information			
Features	High Impact Resistance		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	3.5	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale, Injection Molded)	112		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield, Injection Molded)	29.0	MPa	ASTM D638
Tensile Elongation (Break, Injection Molded)	60	%	ASTM D638
Flexural Modulus (Injection Molded)	1860	MPa	ASTM D790
Flexural Strength (Injection Molded)	41.4	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (Injection Molded)	110	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed, Injection Molded)	77.8	°C	ASTM D648
Vicat Softening Temperature	104	°C	ASTM D1525 <sup>1</sup>
Flammability	Nominal Value		Test Method
Flame Rating	HB		UL 94
NOTE			
1.	Loading 1 (10 N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT