Etinox® EF-0127

Rigid Polyvinyl Chloride

Ercros, S.A.

Message:

Etinox® EF-0127 is a Rigid Polyvinyl Chloride product. It can be processed by injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

| General Information | | | |
|--------------------------------|-------------------|-------|-------------|
| Processing Method | Injection Molding | | |
| Physical | Nominal Value | Unit | Test Method |
| Density (23°C) | 1.38 | g/cm³ | ISO 1183 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Stress | 46.1 | MPa | ISO 527-2 |
| Tensile Strain (Break) | 170 | % | ISO 527-2 |
| Impact | Nominal Value | Unit | Test Method |
| Unnotched Izod Impact Strength | 93 | kJ/m² | ISO 180 |
| Thermal | Nominal Value | Unit | Test Method |
| Vicat Softening Temperature | 80.0 | °C | ISO 306/B |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

