

# Gallonprene® GP550-7504

Thermoplastic Elastomer

Shenzhen Sungallon Rubber & Plastic Corporation Limited

Message:

Gallonprene® GP550-7504 is a Thermoplastic Elastomer (TPE) product. It can be processed by extrusion or profile extrusion and is available in Africa & Middle East, Asia Pacific, or Latin America. Typical application: Sealing Applications.

Characteristics include:

- REACH Compliant
- RoHS Compliant
- Good Aesthetics
- Halogen Free
- Weldable

General Information	
Features	Good Surface Finish
	Halogen Free
	Microbe Resistant
	Weldable
Uses	Profiles
	Seals
Agency Ratings	EC 1907/2006 (REACH)
RoHS Compliance	RoHS Compliant
Appearance	White
Processing Method	Extrusion
	Profile Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.21	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (200°C/10.0 kg)	10	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 23°C)	75		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength <sup>1</sup> (Break)	7.00	MPa	ASTM D412
Tensile Elongation <sup>2</sup> (Break)	550	%	ASTM D412
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	120 to 140	°C	
Cylinder Zone 2 Temp.	130 to 150	°C	
Cylinder Zone 3 Temp.	140 to 160	°C	
NOTE			
1.	500 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

