

Melthene® -M M5311

Polyolefin

TOSOH Corporation

Message:

Melthene® -M M5311 is a Polyolefin material. It is available in Asia Pacific, Europe, or North America for coating, extrusion, or laminating. Primary attribute of Melthene® -M M5311: Good Adhesion.

Typical applications include:

Fabrics/Fibers

Packaging

Sealing Applications

General Information			
Features	Good Adhesion		
Uses	Packaging		
	Sealing Devices		
	Textile Applications		
Forms	Pellets		
Processing Method	Coating		
	Extrusion		
	Laminating		
Physical	Nominal Value	Unit	Test Method
Density	0.940	g/cm ³	ASTM D1505
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	118	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

