

Spartech Polycom E65060

Polyvinyl Chloride

Spartech Polycom

Message:

Spartech Polycom, Kearny is the first choice for compounds meeting the stringent requirements of Spiral Hose, Automotive, Housewares, Farm Equipment, Coated Fencing and numerous other applications including Lawn & Garden Wheels. Our products are engineered specifically for each application, as well as for each customer's equipment, including the demands of today's sophisticated manufacturing processes.

General Information	
Features	General
Uses	Pipe fittings
	Profile
Appearance	Clear/transparent
Processing Method	Co-extrusion molding
	Profile extrusion molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.17	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	60		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	4.07	MPa	ASTM D412
Tensile Strength (Yield)	11.0	MPa	ASTM D412
Tensile Elongation (Break)	470	%	ASTM D412
Additional Information	Nominal Value	Unit	
Stock Temperature	154	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 1342475533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT