

# Shandong PA66 A2G6304

Polyamide 66

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PA66 A2G6304 is a Polyamide 66 (Nylon 66) material filled with filler. It is available in Asia Pacific.  
Typical application of Shandong PA66 A2G6304: Automotive

General Information		
Filler / Reinforcement	Filler	
Features	Hydrolysis Resistant	
Uses	Automotive Applications	
Physical	Nominal Value	Unit
Ash Content	30	%
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	165	MPa
Tensile Strain (Break)	3.0	%
Flexural Modulus	8000	MPa
Flexural Stress	235	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength	12	kJ/m²
Charpy Unnotched Impact Strength	70	kJ/m²

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT