

NORDEL™ IP 3640N

Ethylene Propylene Diene Terpolymer
The Dow Chemical Company

Message:

NORDEL™ IP 3640N Hydrocarbon Rubber is ethylene-propylene-diene terpolymer (EPDM) synthesized by Metallocene Catalyst.

Properties:

- Amorphous
- Very low diene
- Heat and UV stability
- Medium Mooney viscosity

Features:

- Good Processability
- Excellent co-vulcanization with butyl rubber
- High mechanical strength
- Good low temperature flexibility

General Information			
Forms	bag		
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity (ML 1+4, 125°C)	40	MU	ASTM D1646
Ethylene Content	55.0	wt%	ASTM D3900
Additional Information			

Storage and Handling:The quality of EPDM products may be affected by exposure to artificial or natural light. This product should be stored indoors in its original packaging and out of direct sunlight.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT