EVERLON® TS-65

Styrene Ethylene Butylene Styrene Block Copolymer

Ever Polymer Co., Ltd.

Message:

Generally grade: Base on SEBS. suitable for insert molding, excellent bonding PP. All kinds of hardness are prepared very well, excellent weatherability, stability of UV and the physical mechanical property.

| General Information | | | |
|------------------------------|-------------------------|-------|-------------|
| Features | Bondability | | |
| | Good Weather Resistance | | |
| | | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 0.998 | g/cm³ | ASTM D792 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A) | 65 | | ASTM D2240 |
| Elastomers | Nominal Value | Unit | Test Method |
| Tensile Strength | 4.90 | MPa | ASTM D412 |
| Tensile Elongation (Break) | 550 | % | ASTM D412 |
| Tear Strength | 29.4 | kN/m | ASTM D624 |
| Thermal | Nominal Value | Unit | Test Method |
| Brittleness Temperature | -40.0 | °C | ASTM D746 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

