

COSMOTHENE® F410-7

Low Density Polyethylene

TPC, The Polyolefin Company (Singapore) Pte Ltd

Message:

COSMOTHENE F410-7 has excellent transparency, good stiffness and processibility. BHT is not used and it is formulated with medium level of slip and antiblocking agent.

Transparent thin gauge bag, shopping bag, zipper bag and many others general purpose bag.

General Information			
Additive	Moderate caking resistance		
	Moderate smoothness		
Features	Rigid, good		
	Workability, good		
	Definition, high		
	Moderate caking resistance		
	Moderate smoothness		
Uses	Bags		
Agency Ratings	FDA 21 CFR 177.1520(c) 2.1		
Appearance	Clear/transparent		
Forms	Particle		
Processing Method	Film extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.923	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	5.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	13.7	MPa	ASTM D638
Tensile Elongation (Break)	550	%	ASTM D638
Apparent Bending Modulus	240	MPa	ASTM D747
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	30	µm	
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	111	°C	Internal method
Optical	Nominal Value	Unit	Test Method
Gloss (30.0 µm)	120		ASTM D2457
Haze (30.0 µm)	4.0	%	ASTM D1003
Additional Information	Nominal Value	Unit	Test Method
Blocking (30.0 µm)	30.0	g/100 cm ²	ASTM D3354
Slip (30.0 µm)	0.140	Tan θ	Internal method
Extrusion	Nominal Value	Unit	

Cylinder Zone 1 Temp.	130	°C
Cylinder Zone 2 Temp.	145	°C
Cylinder Zone 3 Temp.	155	°C
Melt Temperature	160	°C
Die Temperature	160	°C

Extrusion instructions

Extruder: 50 mm diameter; L/D: 26; C.R: 3.4H Temperature: 160°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT