

Evermore PUR SS-1029MP

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SS-1029MP is a Polyurethane product. It is available in Asia Pacific. Applications of Evermore PUR SS-1029MP include coating applications and fabrics/fibers.

General Information			
Features	Moisture Permeability		
	Soft		
Uses	Coating Applications		
	Textile Applications		
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	3.92 to 5.88	MPa	ASTM D412
Tensile Strength (Yield)	11.8 to 24.5	MPa	ASTM D412
Tensile Elongation (Break)	300 to 600	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	50.0 to 80.0	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	27 to 29	%	
Solvents	DMF, IPA		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

