

Shandong PA66 FRGFPA66

Polyamide 66

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PA66 FRGFPA66 is a Polyamide 66 (Nylon 66) material. It is available in Asia Pacific.

Important attributes of Shandong PA66 FRGFPA66 are:

Flame Rated

Heat Resistant

Wear Resistant

Typical application of Shandong PA66 FRGFPA66: Appliances

General Information		
Features	Combustion Resistant	
	Good Wear Resistance	
	High Heat Resistance	
Uses	Appliance Components	
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	100	MPa
Tensile Strain (Break)	3.0	%
Flexural Stress	100	MPa
Impact	Nominal Value	Unit
Notched Izod Impact Strength	8.0	kJ/m ²
Thermal	Nominal Value	Unit
Heat Deflection Temperature (0.45 MPa, Unannealed)	250	°C
Flammability	Nominal Value	Test Method
Flame Rating	V-0	UL 94
Additional Information	Nominal Value	Unit
Residue of Combustion	28 to 32	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT