Vistalon™ 6602

Ethylene Propylene Diene Terpolymer Rubber

ExxonMobil Chemical

Message:

Vistalon 6602 EPDM is a medium ENB polymer with low ethylene content and medium to high Mooney viscosity. It has a wide molecular weight distribution and can achieve excellent combination processability. It is suitable for extrusion molding products (such as window sealing strips or hoses), and has high collapse resistance and smooth surface. It is also suitable for forming fields that require good resistance to permanent compression deformation.

General Information			
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity ¹ (ML 1+4, 125°C)	80	MU	ASTM D1646
Ethylene Content	55.0	wt%	ASTM D3900
Ethylidene Norbornene (ENB) Content	5.2	wt%	ASTM D6047
Legal statement			

未经埃克森美孚化工书面允许,这种产品包括其产品名称,不得在任何医疗应用领域予以使用或有关详细的产品监管信息,请联系客户服务.

NOTE

Radial cavity mold, polymer re-refined at 145±10°C

1.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

