

Fixmaster Ceramic Tile Adhesive

Epoxy; Epoxide

Loctite®

Message:

Fixmaster Ceramic Tile Adhesive is an Epoxy; Epoxide (Epoxy) product. It is available in North America. Typical application: Adhesives/Tapes.

Characteristics include:

High Strength

Impact Resistant

General Information			
Features	Fast Cure		
	Good Impact Resistance		
	High Strength		
Uses	Adhesives		
	Bonding		
Appearance	Brown		
Forms	Pellets		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	34.5	MPa	ASTM D638
Compressive Modulus	96.5	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	93.3	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Volume: 1.0		
Resin	Mix Ratio by Volume: 1.0		
Pot Life (25°C)	1.0	min	
Demold Time (25°C)	240	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT