

Varcum 29159

Phenolic

Durez Corporation

Message:

Varcum 29159 is a liquid one-step, phenolic resin in a mixture of xylol and butanol.
Metal coating applications involving the formulation of phenolic resins with epoxy resins and similar modifiers.
Exhibits good compatability with epoxy resins.
Offers good, inherent flexibility characteristics.
Provides light color.
Promotes good adhesion to metal.
Medium rate of cure allows maximum solvent evaporation before curing minimizing coating problems.

| General Information | | | |
|--------------------------------|----------------------|------|-----------------|
| Features | Good Adhesion | | |
| | Good Flexibility | | |
| Uses | Coating Applications | | |
| Forms | Liquid | | |
| Physical | Nominal Value | | Test Method |
| Color | < 10 | | Internal Method |
| Non-Volatile Content | 50 | % | Internal Method |
| Thermoset | Nominal Value | Unit | Test Method |
| Thermoset Mix Viscosity (25°C) | 120 | cP | Internal Method |
| Post Cure Time (185°C) | 0.017 | hr | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT