

# Naxel PC530-112

Polycarbonate

Custom Resins Group

Message:

General purpose, UV stabilized polycarbonate molding resin

Has the high impact resistance and heat resistance typical of polycarbonate, while adding a UV stabilizer package for improved weatherability

Suitable for enclosures and housings, trim panels, and consumer items that may experience increased light exposure

General Information	
Additive	UV Stabilizer
Features	General Purpose
	Good Weather Resistance
	High Heat Resistance
	High Impact Resistance
Uses	General Purpose
	Housings

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.20	g/cm <sup>3</sup>	ASTM D792
Molding Shrinkage - Flow	0.60	%	ASTM D955
Viscosity	17 melt flow		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	58.2	MPa	ASTM D638
Tensile Elongation (Yield)	65	%	ASTM D638
Flexural Modulus	2330	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	720	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT