

Kafrit PEX TA 2114 HD

Crosslinked Polyethylene

Kafrit NA Ltd.

Message:

TA 2114 HD catalyst masterbatch is used with Kafrit NA cross-linkable PEX-b compound TA 1117 HD to produce pipe, tubing and various profiles. TA 2114 HD contains a crosslinking catalyst which will complete the Sioplas System when extruded with PEX-b compounds such as TA 1117 HD. TA 2114 HD contains additives which protect the finished product from long term degradation caused by oxidation and heat.

General Information		
Additive	Antioxidant	
	Heat Stabilizer	
Features	Antioxidant	
	Heat Stabilized	
	Non-Toxic	
Uses	Masterbatch	
	Oil/Gas Applications	
	Piping	
	Potable Water Applications	
	Profiles	
	Tubing	
Agency Ratings	NSF 61	
Appearance	Natural Color	
	Translucent	
Forms	Pellets	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Density	0.970	g/cm ³
Apparent Density	0.55	g/cm ³
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	7.5	g/10 min
Additional Information	Nominal Value	Unit
Volatiles	< 0.15	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

