

Hostacom M2 T02 102942

Polypropylene Homopolymer

LyondellBasell Industries

Message:

Hostacom M2 T02 102942 is a 20% talc filled PP homopolymer, with high flowability. The product is available in different color matched, pellet form. This grade is delivered in 102942 color version.

This grade is not intended for medical, pharmaceutical, food and drinking water applications.

General Information			
Filler / Reinforcement	Talc filler, 20% filler by weight		
Features	Homopolymer		
	Good liquidity		
	High liquidity		
Uses	Parts under the hood of a car		
	Application in Automobile Field		
Appearance	Available colors		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.04	g/cm ³	ISO 1183/A
Melt Mass-Flow Rate (MFR)			ISO 1133
230°C/2.16 kg	6.0	g/10 min	ISO 1133
230°C/5.0 kg	26	g/10 min	ISO 1133
Melt Volume-Flow Rate (MVR)			ISO 1133
230°C/2.16 kg	7.00	cm ³ /10min	ISO 1133
230°C/5.0 kg	30.0	cm ³ /10min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (23°C)	2700	MPa	ISO 527-2
Tensile Stress (Yield, 23°C)	33.0	MPa	ISO 527-2
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	4.0	kJ/m ²	ISO 179/1eA
Charpy Unnotched Impact Strength (23°C)	40	kJ/m ²	ISO 179/1eU

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

