YUPLENE® B340F

Polypropylene Impact Copolymer

SK Global Chemical

Message:

YUPLENE B340F is a propylene impact copolymer designed for injection molding applications. YUPLENE B340F has excellent toughness, good dimensional stability and has been listed by Underwriters Laboratories (UL). YUPLENE B340F is suitable for household articles, electric appliances, battery cases and various containers.

YUPLENE B340F complies with FDA regulation 21 CFR177.1520.

General Information				
UL YellowCard	E135809-222658			
Features	Good Dimensional Stability			
	Good Toughness			
	High Impact Resistance			
	Impact Copolymer			
Uses	Appliance Components			
	Automotive Applications			
	Battery Cases			
	Containers			
	Household Goods			
Agency Ratings	FDA 21 CFR 177.1520			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Melt Mass-Flow Rate (MFR) (230°C/2.16				
kg)	7.0	g/10 min	ASTM D1238	
Spiral Flow	68.0	cm	Internal Method	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	85		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	26.0	MPa	ASTM D638	
Tensile Elongation (Break)	> 500	%	ASTM D638	
Flexural Modulus	1180	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact			ASTM D256	
-20°C	69	J/m		
23°C	150	J/m		
Aging	Nominal Value	Unit	Test Method	
Accelerated Oven Aging - in Air (150°C)	15.0	day	ASTM D3012	
Heat Deflection Temperature	110	°C	ASTM D648	

DuPont Impact Strength (-10°C)	> 2.94	J	ASTM D2794
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	150	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

