

# Fixmaster Marine Chocking

Epoxy; Epoxide

Loctite®

## Message:

Fixmaster Marine Chocking is an Epoxy; Epoxide (Epoxy) product. It is available in North America. Typical application: Construction Applications.

Characteristics include:

Chemical Resistant

Low Shrinkage

| General Information        |                             |      |             |
|----------------------------|-----------------------------|------|-------------|
| Features                   | Fast Cure                   |      |             |
|                            | Good Chemical Resistance    |      |             |
|                            | Low Shrinkage               |      |             |
|                            | Vibration Damping           |      |             |
| Uses                       | Flooring Maintenance/Repair |      |             |
| Appearance                 | Green                       |      |             |
|                            | Yellow                      |      |             |
| Forms                      | Pellets                     |      |             |
| Mechanical                 | Nominal Value               | Unit | Test Method |
| Tensile Strength (Yield)   | 37.9                        | MPa  | ASTM D638   |
| Compressive Strength       | 124                         | MPa  | ASTM D695   |
| Thermal                    | Nominal Value               | Unit | Test Method |
| Continuous Use Temperature | 121                         | °C   | ASTM D794   |
| Thermoset                  | Nominal Value               | Unit |             |
| Pot Life (25°C)            | 10 to 15                    | min  |             |
| Demold Time (25°C)         | 1400                        | min  |             |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT