

Sylvin 2986-60 White 1577

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:
Sylvin 2986-60 White 1577 Is A Compound Formulated With FDA Sanctioned Ingredients. It Contains A Non Ortho Phthalate Plasticizer And A High Molecular Weight Resin For Increased Flexibility In Inner Core Hose Applications.

General Information			
Additive	Plasticizer		
Features	Non-phthalate plasticizer		
	High molecular weight		
Uses	Pipe		
Agency Ratings	FDA not rated		
Appearance	White		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.16	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	60		ASTM D2240
Shaw A, 10 seconds	60		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	11.4	MPa	ASTM D638
Tensile Elongation (Break)	380	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	35.0	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	171 - 188	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT