

Jam PE 20X02

Linear Low Density Polyethylene

Jam Petrochemical Company

Message:

Jam PE 20X02 is a Linear Low Density Polyethylene product. It can be processed by cast film and is available in Africa & Middle East. Typical application: Bags/Liners.

General Information			
Features	Terpolymer		
Uses	Bags		
	General Purpose		
Processing Method	Cast Film		
Physical	Nominal Value	Unit	Test Method
Density	0.920 to 0.922	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.5	g/10 min	ASTM D1238
Flow Rate Ratio	32.0		ASTM D1238
Fish Eye	60.0	No./m ²	
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	25	µm	
Dart Drop Impact (25 µm, Blown Film)	30	g	ASTM D1709A
Elmendorf Tear Strength			ASTM D1922
MD : 25 µm, Blown Film	30	g	
TD : 25 µm, Blown Film	210	g	
Optical	Nominal Value	Unit	Test Method
Gloss (45°, 25.0 µm, Blown Film)	75		ASTM D1790
Haze (25.0 µm, Blown Film)	4.0	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT