Braskem PP CP 270R

Polypropylene Impact Copolymer

Braskem

Message:

CP 270R is an ethene and propene heterophasic copolymer specially designed for injection molding of pails and containers with excellent stiffness/impact strength balance. This resin also exhibits excellent productivity and processability.

Applications

Injection with good mechanical strength; Household; Industrial Pails.

Processing:

Injection Moulding

General Information					
Features	Good Processability				
	High Impact Resistance				
	High Stiffness				
	Impact Copolymer				
Uses	Containers				
	Household Goods				
	Pails				
Agency Ratings	FDA 21 CFR 177.1520				
Processing Method	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	0.900	g/cm³	ASTM D792		
Melt Mass-Flow Rate (MFR)					
230°C/2.16 kg	20	g/10 min	ASTM D1238		
230°C/2.16 kg	21	g/10 min	ISO 1133		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (Injection Molded)	65		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield, Injection Molded)	26.0	MPa	ASTM D638		
Tensile Elongation (Yield, Injection					
Molded)	6.0	%	ASTM D638		
Flexural Modulus - 1% Secant					
Injection Molded	1200	MPa	ASTM D790		
Injection Molded	1300	MPa	ISO 178		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact					
-20°C, Injection Molded	55	J/m	ASTM D256		
23°C, Injection Molded	250	J/m	ASTM D256		
-20°C, Injection Molded	6.0	kJ/m²	ISO 180		

23°C, Injection Molded	12	kJ/m²	ISO 180
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45			
MPa, Unannealed, Injection Molded)	108	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

