

CGPC PVC H-58

Polyvinyl Chloride

China General Plastics Corporation

Message:

CGPC PVC H-58 is a Polyvinyl Chloride material. It is available in Asia Pacific or North America for blow molding or injection molding.

Typical applications include:

Bottles

Engineering/Industrial Parts

General Information			
Uses	Blow Molding Applications		
	Bottles		
	Fittings		
Processing Method	Blow Molding		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.53 to 0.61	g/cm ³	ISO 60
K-Value	57.0 to 59.0		ISO 1628-2
Particle Size - 45 Mesh Pass ¹	> 99.0	%	
Degree of Polymerization	650 to 750		
Residual Vinyl Chloride Monomer	< 1	ppm	ISO 6401
Volatiles	< 0.30	%	ISO 1269
NOTE			
1.	Honeywell SRA-150		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

