

# Supol HT125E

Polypropylene Copolymer

LyondellBasell Industries

## Message:

SUPOL HT125E is a filled UV resistant polypropylene copolymer compound for injection moulding. Designed for automotive applications it is available in custom colours.

Typical Customer Applications:

Interior Applications

General Information			
Features	Good UV Resistance		
	High Flow		
	High Rigidity		
Uses	Automotive Applications		
Appearance	Colors Available		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.970	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR)	25	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	1850	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	13	kJ/m <sup>2</sup>	ISO 180/1A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT