Polyrocks 7001A

Acrylonitrile Butadiene Styrene Polyrocks Chemical Co., Ltd

Message:

7001(+) is environmental flame retardant ABS with environmental bromine-antimony flame retardant system. Adopting the advanced processing technology to ensure flame ratardant effect and have good rigidity and toughness. Environmental flame retardant ABS has passed SGS, CTI tests, and meets the requirements of RoHS, SVHC, PFOS & PFOA, 16P, PAHs...etc.

Flame retardant ABS7001A: high impact strength, good toughness.

Application: shells and panels of electronic appliances, outer panels of automotive...etc.

Additive Flame retardancy 2 Features Good Rigidity (mpact resistance, high (Good toughness) (Flame retardancy) Cood toughness (Flame retardancy) Uses Electrical/Electronic Applications (Amount of Electrical/Electronic Applications (Amount of Electronic Amount of Electronic	General Information				
Impact resistance, high Good toughness Flame retardancy Less Electrical/Electronic Applications Home appliance components Car exterior decoration EC 1907/2006 (REACH) ROHS Compliance ROHS Compliance ROHS Compliance Physical Nominal Value Melt Mass-Flow Rate (MFR) Flow ASTM D792 Melt Mass-Flow Rate (MFR) Flow Bollance ROHS Compliance Nominal Value Milt Mass-Flow Rate (MFR) Flow Bollance Rohs Compliance Rohs Rohs Rohs Rohs Rohs Rohs Rohs Rohs	Additive	Flame retardancy 2			
Good toughness Flame retardancy Flame retardancy	Features	Good Rigidity			
Flame retardancy Flame retardancy Flame retardancy Flame retardancy Flame appliance components Florme appliance Florme appl		Impact resistance, high			
		Good toughness	Good toughness		
Agency Ratings EC 1907/2006 (REACH) ROHS Compliance Forms Particles Physical Nominal Value Unit Test Method Specific Gravity 1.18 9/10 min ASTM D1238 Mechanical Nominal Value Unit Test Method Tensile Strength 45.0 MPa ASTM D638 Flexural Modulus 45.0 MPa ASTM D638 Flexural Modulus 45.0 MPa ASTM D638 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Physical Nominal Value Unit Test Method Tensile Elongation (Break) 30 MPa ASTM D638 Flexural Strength 55.0 MPa ASTM D638 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa ASTM D790 Impact Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa ASTM D556 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflex Unit Mpa		Flame retardancy			
Agency Ratings EC 1907/2006 (REACH) ROHS Compliance Forms Particles Physical Nominal Value Unit Test Method Specific Gravity 1.18 9/10 min ASTM D1238 Mechanical Nominal Value Unit Test Method Tensile Strength 45.0 MPa ASTM D638 Flexural Modulus 45.0 MPa ASTM D638 Flexural Modulus 45.0 MPa ASTM D638 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Physical Nominal Value Unit Test Method Tensile Elongation (Break) 30 MPa ASTM D638 Flexural Strength 55.0 MPa ASTM D638 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa ASTM D790 Impact Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa ASTM D556 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) Unit Test Method Deflex Unit Mpa					
Agency Ratings	Uses	Electrical/Electronic Applications			
Agency Ratings EC 1907/2006 (REACH) RoHS Compliance RoHS compliance Forms Particles Physical Nominal Value Unit Test Method Specific Gravity 1.18 g/cm³ ASTM D792 Melt Mass-Flow Rate (MFR) 60 g/10 min ASTM D1238 Mechanical Nominal Value Unit Test Method Tensile Strength 45.0 MPa ASTM D638 Flexural Modulus 2400 MPa ASTM D790 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D56 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 *C ASTM D648 Flanmability Nominal Value Unit Test Method Flanma Rating **C ASTM D648 Flanma Rating **C ASTM D648 Flanma Rating <t< td=""><td rowspan="2"></td><td colspan="3">Home appliance components</td></t<>		Home appliance components			
RoHS Compliance RoHS compliance Forms Particles Physical Nominal Value Unit Test Method Specific Gravity 1.18 g/cm³ ASTM D792 Melt Mass-Flow Rate (MFR) 60 g/10 min ASTM D1238 Mechanical Nominal Value Unit Test Method Tensile Strength 45.0 MPa ASTM D638 Flexural Modulus 2400 MPa ASTM D638 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45) \$5.0 °C ASTM D648 Flammability Nominal Value Unit Test Method Flammability Nominal Value Unit Test Method Flammability Nominal Value Unit Test Method 1.5 mm V-0 Unit		Car exterior decoration			
RoHS Compliance RoHS compliance Forms Particles Physical Nominal Value Unit Test Method Specific Gravity 1.18 g/cm³ ASTM D792 Melt Mass-Flow Rate (MFR) 60 g/10 min ASTM D1238 Mechanical Nominal Value Unit Test Method Tensile Strength 45.0 MPa ASTM D638 Flexural Modulus 2400 MPa ASTM D638 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45) \$5.0 °C ASTM D648 Flammability Nominal Value Unit Test Method Flammability Nominal Value Unit Test Method Flammability Nominal Value Unit Test Method 1.5 mm V-0 Unit					
FormsParticlesPhysicalNominal ValueUnitTest MethodSpecific Gravity1.18g/cm³ASTM D792Melt Mass-Flow Rate (MFR)60g/10 minASTM D1238MechanicalNominal ValueUnitTest MethodTensile Strength45.0MPaASTM D638Tensile Elongation (Break)30%ASTM D790Flexural Modulus2400MPaASTM D790Flexural Strength55.0MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact300J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45) MPa, Unannealed)85.0°CASTM D648FlammabilityNominal ValueUnitTest MethodFlame RatingUnitTest Method1.5 mmV-0UnitUnitTest Method1.5 mmV-0UnitUnitUnit	Agency Ratings	EC 1907/2006 (REACH)	EC 1907/2006 (REACH)		
Physical Nominal Value Unit Test Method Specific Gravity 1.18 g/cm³ ASTM D792 Melt Mass-Flow Rate (MFR) 60 g/10 min ASTM D1238 Mechanical Nominal Value Unit Test Method Tensile Strength 45.0 MPa ASTM D638 Tensile Elongation (Break) 30 % ASTM D790 Flexural Modulus 2400 MPa ASTM D790 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 °C ASTM D648 Flammability Nominal Value Unit Test Method Flame Rating V-0 UL 94 UL 94 1.5 mm V-0 U.0 UL 94	RoHS Compliance	RoHS compliance	RoHS compliance		
Specific Gravity 1.18 g/cm³ ASTM D792 Melt Mass-Flow Rate (MFR) 60 g/10 min ASTM D1238 Mechanical Nominal Value Unit Test Method Tensile Strength 45.0 MPa ASTM D638 Tensile Elongation (Break) 30 % ASTM D638 Flexural Modulus 2400 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 °C ASTM D648 Flammability Nominal Value Unit Test Method Flame Rating Unit Test Method 1.5 mm V-0 Unit Unit	Forms	Particles			
Melt Mass-Flow Rate (MFR) 60 g/10 min ASTM D1238 Mechanical Nominal Value Unit Test Method Tensile Strength 45.0 MPa ASTM D638 Tensile Elongation (Break) 30 % ASTM D638 Flexural Modulus 2400 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 °C ASTM D648 Flammability Nominal Value Unit Test Method Flame Rating Unit Test Method 1.5 mm V-0 Unit Unit	Physical	Nominal Value	Unit	Test Method	
MechanicalNominal ValueUnitTest MethodTensile Strength45.0MPaASTM D638Tensile Elongation (Break)30%ASTM D638Flexural Modulus2400MPaASTM D790Flexural Strength55.0MPaASTM D790ImpactNominal ValueUnitTest MethodNotched Izod Impact300J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed)85.0°CASTM D648FlammabilityNominal ValueUnitTest MethodFlame RatingV-0UnitUnitUnit1.5 mmV-0UnitUnitUnit1.5 mmV-0UnitUnitUnit	Specific Gravity	1.18	g/cm³	ASTM D792	
Tensile Strength 45.0 MPa ASTM D638 Tensile Elongation (Break) 30 % ASTM D638 Flexural Modulus 2400 MPa ASTM D790 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 °C ASTM D648 Flammability Nominal Value Unit Test Method Flame Rating Unit Test Method Unit Unit Test Method Unit Unit Test Method Unit Unit Unit Unit Unit Unit Unit Unit	Melt Mass-Flow Rate (MFR)	60	g/10 min	ASTM D1238	
Tensile Elongation (Break) 30 % ASTM D638 Flexural Modulus 2400 MPa ASTM D790 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Peflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 °C ASTM D648 Flammability Nominal Value Unit Test Method Flame Rating UL 94 1.5 mm V-0 UL 94 2.0 mm V-0 UL 94	Mechanical	Nominal Value	Unit	Test Method	
Flexural Modulus 2400 MPa ASTM D790 Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 °C ASTM D648 Flammability Nominal Value Unit Test Method I.5 mm V-0 UL 94 2.0 mm V-0 UL 94	Tensile Strength	45.0	MPa	ASTM D638	
Flexural Strength 55.0 MPa ASTM D790 Impact Nominal Value Unit Test Method Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 °C ASTM D648 Flammability Nominal Value Unit Test Method Flame Rating UL 94 1.5 mm V-0 UL 94 2.0 mm	Tensile Elongation (Break)	30	%	ASTM D638	
ImpactNominal ValueUnitTest MethodNotched Izod Impact300J/mASTM D256ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed)85.0°CASTM D648FlammabilityNominal ValueUnitTest MethodFlame RatingUL 941.5 mmV-0UL 942.0 mmV-0UL 94	Flexural Modulus	2400	MPa	ASTM D790	
Notched Izod Impact 300 J/m ASTM D256 Thermal Nominal Value Unit Test Method Deflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 °C ASTM D648 Flammability Nominal Value Unit Test Method 1.5 mm V-0 UL 94 2.0 mm V-0 UL 94	Flexural Strength	55.0	MPa	ASTM D790	
ThermalNominal ValueUnitTest MethodDeflection Temperature Under Load (0.45 MPa, Unannealed)85.0℃ASTM D648FlammabilityNominal ValueUnitTest MethodFlame RatingUL 941.5 mmV-0UL 942.0 mmV-0UL 94	Impact	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (0.45 MPa, Unannealed) 85.0 C Flammability Nominal Value Unit Test Method UL 94 1.5 mm V-0 V-0 UL 94	Notched Izod Impact	300	J/m	ASTM D256	
MPa, Unannealed)85.0°CASTM D648FlammabilityNominal ValueUnitTest MethodFlame RatingUL 941.5 mmV-0UL 942.0 mmV-0UL 94	Thermal	Nominal Value	Unit	Test Method	
Flame Rating 1.5 mm V-0 UL 94 2.0 mm V-0 UL 94	· ·		°C	ASTM D648	
1.5 mm V-0 UL 94 2.0 mm V-0 UL 94	Flammability	Nominal Value	Unit	Test Method	
2.0 mm V-0 UL 94	Flame Rating			UL 94	
	1.5 mm	V-0		UL 94	
3.0 mm 5VA UL 94	2.0 mm	V-0		UL 94	
	3.0 mm	5VA		UL 94	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

850

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

