

# Fixmaster Conveyor Belt Repair

Polyurethane

Loctite®

## Message:

Fixmaster Conveyor Belt Repair is a Polyurethane product. It is available in North America. Applications of Fixmaster Conveyor Belt Repair include engineering/industrial parts and repairing material.

Characteristics include:

Good Flexibility

Wear Resistant

General Information			
Features	Good Abrasion Resistance		
	Good Flexibility		
Uses	Belts/Belt Repair		
	Repairing Material		
Appearance	Black		
Forms	Pellets		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	10.3	MPa	ASTM D638
Tensile Elongation (Yield)	200	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	93.3	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Pot Life (25°C)	10 to 15	min	
Demold Time (25°C)	480 to 720	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT