

KEP® 281F

Ethylene Propylene Diene Terpolymer

Kumho Polychem Co., Ltd.

Message:

Features:

High mooney viscosity & high vulcanization speed, high filler loading & excellent extrusion property, good collapse resistance

Applications:

Weatherstrip solid, window seals, various types of automobile parts, heat resistant hose

General Information		
Features	High Viscosity	
	Vulcanizable	
Uses	Automotive Applications	
	Hose	
	Seals	
	Weatherstripping	
	Windows & Doors	
Forms	Bale	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Mooney Viscosity (ML 1+8, 125°C)	82	MU
Ethylene Content	67.0	wt%
Ethylidene Norbornene (ENB) Content	5.7	wt%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

