

# Trademark PE LD2923F

Low Density Polyethylene  
Trademark Plastics Corporation

Message:

Trademark PE LD2923F is a Low Density Polyethylene product. It is available in North America. Applications of Trademark PE LD2923F include bags/liners, engineering/industrial parts, film and food contact applications.

Characteristics include:

- Antiblock
- Clarity
- Food Contact Acceptable
- Good Processability
- Good Sealability

General Information			
Additive	Medium Antiblock		
	Medium Slip		
Features	Food Contact Acceptable		
	Good Heat Seal		
	Good Processability		
	High Clarity		
	High Strength		
	Medium Antiblocking		
	Medium Slip		
Uses	Bags		
	Film		
	Heavy-duty Bags		
	Laundry Bags		
	Transparent Parts		
Agency Ratings	FDA 21 CFR 177.1520(c) 2.1		
Physical	Nominal Value	Unit	Test Method
Density	0.923	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	51	µm	ASTM D882
Secant Modulus			
1% Secant, MD : 51 µm, Blown Film	172	MPa	
1% Secant, TD : 51 µm, Blown Film	200	MPa	ASTM D882
Tensile Strength			
MD : Break, 51 µm,Blown Film	24.1	MPa	

TD : Break, 51 μm,Blown Film	18.6	MPa	
Tensile Elongation			ASTM D882
MD : Break, 51 μm,Blown Film	350	%	
TD : Break, 51 μm,Blown Film	700	%	
Dart Drop Impact (51 μm, Blown Film)	100	g	ASTM D1709
Elmendorf Tear Strength			ASTM D1922
MD : 51 μm, Blown Film	360	g	
TD : 51 μm, Blown Film	200	g	
Optical	Nominal Value	Unit	Test Method
Gloss (45°, 50.8 μm, Blown Film)	76		ASTM D2457
Haze (50.8 μm, Blown Film)	5.0	%	ASTM D1003
Extrusion	Nominal Value	Unit	
Melt Temperature	182 to 199	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

